

**SR 200-12/24**

Systeemspanning <i>Circuit voltage</i>	12 and 24Vdc, auto detect
Ingangspanningbereik <i>Inputvoltage range</i>	9-35Vdc
Aantal accu aansluitingen <i>Number of batteries</i>	2
Maximale belasting continu <i>Max. load output, continuously</i>	12Vdc: 200Amp. @ 20°C 24Vdc: 100Amp. @ 20°C
Maximale piek belasting <i>Max. surge load</i>	12Vdc: 500Amp. (1sec.) @ 20°C 24Vdc: 250Amp. (1sec.) @ 20°C
Inschakelvoorwaarden <i>Switch on details</i>	12Vdc: PIN 30 or 87 $\geq$ 13,2Vdc for 10sec. PIN 30 or 87 $\geq$ 13,8Vdc for 2sec. 24Vdc: PIN 30 or 87 $\geq$ 26,4Vdc for 10sec. PIN 30 or 87 $\geq$ 27,6Vdc for 2sec.
Afschakelvoorwaarden <i>Switch off details</i>	12Vdc: PIN 30 or 87 $\leq$ 12,8Vdc for 60sec. PIN 30 or 87 $\leq$ 12,5Vdc for 30sec. PIN 30 or 87 $\leq$ 12,0Vdc for 5sec. PIN 30 or 87 $\leq$ 11,0Vdc for 0sec. 24Vdc: PIN 30 or 87 $\leq$ 25,6Vdc for 60sec. PIN 30 or 87 $\leq$ 25,0Vdc for 30sec. PIN 30 or 87 $\leq$ 24,0Vdc for 5sec. PIN 30 or 87 $\leq$ 22,0Vdc for 0sec.
Eigen verbruik, uitgeschakeld <i>Current draw, switched on</i>	5mA @ 12/24Vdc
Eigen verbruik, ingeschakeld <i>Current draw, switched off</i>	450mA @ 13,5Vdc 225mA @ 27Vdc
Start assistentie functie <i>Start assist function</i>	Ja, $\geq$ 30 seconden Yes, $\geq$ 30 seconds
Aansluitingen <i>Connections</i>	2x M6 bouten + 2x faston 6,3mm 2x M6 bolts + 2x faston 6,3mm
Omgevingstemperatuur <i>Ambient temperature</i>	-30°C / 60°C
Beschermingsgraad <i>Level of protection</i>	IP 54
Gewicht <i>Weight</i>	100gr.
Afmetingen behuizing <i>Housing dimensions</i>	4,8 x 4,6 x 4,6 cm (behuizing/housing) 4,8 x 7,8 x 4,6 cm (totaal/total)